

Serial No. New Application

REMARKS


Claims 1-15, as amended, remain herein. Claims 3, 7 and 10 have been amended hereby.

This Preliminary Amendment is submitted to eliminate multiply dependent claims from the above-identified application.

Examination of this application on its merits is respectfully requested.

Respectfully submitted,  
PARKHURST & WENDEL, L.L.P.

February 25, 2002  
Date

  
Roger W. Parkhurst  
Registration No. 25,177

RWP/ame

Attorney Docket No. YMOR:238

PARKHURST & WENDEL, L.L.P.  
1421 Prince Street, Suite 210  
Alexandria, Virginia 22314-2805  
Telephone: (703) 739-0220

205220 02209004

## CLAIMS

1. A sensor system for a disk device by using a floating head, comprising:

a rotating disk having a data recording area;

a head element that floats over the data recording area of the disk so as to write data thereon or read data therefrom;

a first actuator for moving the head element over the data recording area of the disk;

a second actuator being supported by the first actuator and supporting the head element for precise positioning thereof against the data recording area of the disk; and

a means for detecting any contact between the disk and the head element, by utilizing a signal generated by the second actuator when the disk contacts the head element during an operation of the disk.

2. The sensor system for a disk device by using a floating head according to Claim 1, wherein the second actuator is a piezoelectric element.

3. The sensor system for a disk device by using a floating head according to Claim 1 ~~or Claim 2~~, wherein the second actuator is disposed on a load beam of a head suspension.

4. A flying height testing method for a disk device by using a floating head, comprising:

the head element is retreated from a disk surface by the first actuator when the disk is not in operation, and the system further comprises a means for detecting a vibration disturbance by utilizing a signal generated by the second actuator due to this vibration disturbance, before the first actuator starts a loading operation of the head element onto the disk surface from a retreat position.

6. The sensor system for a disk device by using a floating head according to Claim 5, wherein the second actuator is a piezoelectric element.

7. The sensor system for a disk device by using a floating head according to Claim 5 ~~or Claim 6~~, wherein the second actuator is disposed on a load beam of a head suspension.

8. A sensor system for a disk device by using a floating head, comprising:

a rotating disk having a data recording area;

a head element that floats over the data recording area of the disk so as to write data thereon or read data therefrom;

a first actuator for moving the head element over the data recording area of the disk;

a second actuator supported by the first actuator and supporting the head element for precisely positioning the head element against the data recording area of the disk;

and

a means for canceling a resonance generated between the head element and the second actuator, by applying to the second actuator a signal having a phase opposite to that of a signal generated by the second actuator when the head element is floating.

9. The sensor system for a disk device by using a floating head according to Claim 8, wherein the second actuator is a piezoelectric element.

10. The sensor system for a disk device by using a floating head according to Claim 8 ~~or Claim 9~~, wherein the second actuator is disposed on a load beam of a head suspension system.

11. A sensor system for a disk device by using a floating head, including a single-plate servo writer, said servo writer comprising:

a head element that floats over a data recording area of a rotating disk so as to write servo information thereon or read servo information therefrom;

a first actuator for moving the head element over the data recording area of the disk;

a second actuator supported by the first actuator and supporting the head element for precisely positioning the head element against the data recording area of the disk;